







Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 10/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 104 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- · Presented in 2 vibrant colors: Orange, Blue.
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14410050BL**

Length **50'**

Description
10/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Blue

Gauge/Conductors

10/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

13A, 123V, 10/3V

Product packaging **Cuff wrapper**

Unit dimensions D x W x H (inches)

12.0 x 3.0 x 12.7

Unit weight (lbs)

5.76

Master carton type

Plain corrugated

Master carton dimensions D x W x H

14.0 x 7.0 x 57

Master carton weight (lbs)

24

Master carton case quantity

4

Master carton cube (cu. ft.)

3.0

UPC

661899 158076

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 10/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 104 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 2 vibrant colors: Orange, Blue.
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14410050GN**

Length **50'**

Cord

Description
10/3 SJTW Pro Lock Extension

Product line

Pro Lock Extension Cord

Color

Green

Gauge/Conductors

10/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings

15A, 125V, 1875W

Product packaging **Cuff wrapper**

Unit dimensions D x W x H (inches)

12.0 x 3.0 x 12.7

Unit weight (lbs)

5.76

Master carton type

Plain corrugated

Master carton dimensions D x W x H

14.0 x 7.0 x 57

Master carton weight (lbs)

24

Master carton case quantity

4

Master carton cube (cu. ft.)

3.0

UPC

661899 159219

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 10/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 104 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 2 vibrant colors: Orange, Blue.
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14410050OR**

Length **50'**

Description
10/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Orange

Gauge/Conductors

10/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

12.0 x 3.0 x 12.7

Unit weight (lbs)

5.76

Master carton type

Plain corrugated

Master carton dimensions D x W x H

14.0 x 7.0 x 57

Master carton weight (lbs)

24

Master carton case quantity

4

Master carton cube (cu. ft.)

3.0

UPC

661899 158090

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 10/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 104 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 2 vibrant colors: Orange, Blue.
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14410100BL**

Length 100'

Description
10/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Blue

Gauge/Conductors

10/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

13.0 x 13.0 x 4.0

Unit weight (lbs)

22.0

Master carton type

Plain corrugated

Master carton dimensions D x W x H

15.0 x 15.0 x 10.5

Master carton weight (lbs)

46

Master carton case quantity

2

Master carton cube (cu. ft.)

1.4

UPC

661899 158083

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 10/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 104 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- · Presented in 2 vibrant colors: Orange, Blue.
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14410100GN**

Length 100'

Cord

Description
10/3 SJTW Pro Lock Extension

Product line

Pro Lock Extension Cord

Color

Green

Gauge/Conductors

10/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

13.0 x 13.0 x 4.0

Unit weight (lbs)

22.0

Master carton type

Plain corrugated

Master carton dimensions D x W x H

15.0 x 15.0 x 10.5

Master carton weight (lbs)

46

Master carton case quantity

2

Master carton cube (cu. ft.)

1.4

UPC

661899 159752

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 10/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 104 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- · Presented in 2 vibrant colors: Orange, Blue.
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14410100OR**

Length 100'

Description
10/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Orange

Gauge/Conductors

10/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

13.0 x 13.0 x 4.0

Unit weight (lbs)

22.0

Master carton type

Plain corrugated

Master carton dimensions $D \times W \times H$

15.0 x 15.0 x 10.5

Master carton weight (lbs)

46

Master carton case quantity

2

Master carton cube (cu. ft.)

1.4

UPC

661899 158106

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 3 vibrant colors: Orange, Blue, Green
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14412050BL**

Length **50'**

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Blue

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

11.5 x 11.5 x 2.5

Unit weight (lbs)

6.5

Master carton type

Plain corrugated

Master carton dimensions $D \times W \times H$

12.0 x 24.0 x 9.0

Master carton weight (lbs)

41

Master carton case quantity

6

Master carton cube (cu. ft.) **1.5**

- ...

UPC

661899 158014

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 3 vibrant colors: Orange, Blue, Green
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14412050GN**

Length **50'**

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Green

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings

15A, 125V, 1875W

Product packaging **Cuff wrapper**

Unit dimensions D x W x H (inches)

11.5 x 11.5 x 2.5

Unit weight (lbs)

6.5

Master carton type

Plain corrugated

Master carton dimensions $D \times W \times H$

12.0 x 24.0 x 9.0

Master carton weight (lbs)

41

Master carton case quantity

6

Master carton cube (cu. ft.)

1.5

UPC

661899 158038

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 3 vibrant colors: Orange, Blue, Green
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14412050OR**

Length **50'**

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Orange

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

11.5 x 11.5 x 2.5

Unit weight (lbs)

6.5

Master carton type

Plain corrugated

Master carton dimensions $D \times W \times H$

12.0 x 24.0 x 9.0

Master carton weight (lbs)

41

Master carton case quantity

6

Master carton cube (cu. ft.)

1.5

UPC

661899 158052

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 3 vibrant colors: Orange, Blue, Green
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number D14412050WH

Length **50'**

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

White

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

11.5 x 11.5 x 2.5

Unit weight (lbs)

6.5

Master carton type

Plain corrugated

Master carton dimensions D x W x H

12.0 x 24.0 x 9.0

Master carton weight (lbs)

41

Master carton case quantity

6

Master carton cube (cu. ft.)

1.5

UPC

661899 159639

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- · Presented in 4 vibrant colors: Orange, Blue, Green & Yellow
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14412050YL**

Length **50'**

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Yellow

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

11.5 x 11.5 x 2.5

Unit weight (lbs)

6.5

Master carton type

Plain corrugated

Master carton dimensions $D \times W \times H$

12.0 x 24.0 x 9.0

Master carton weight (lbs)

41

Master carton case quantity

6

Master carton cube (cu. ft.) **1.5**

- ...

UPC

661899 164916

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock[™] connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 3 vibrant colors: Orange, Blue, Green
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14412100BL**

Length 100'

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Blue

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings **15A, 125V, 1875W**

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

12.0 x 12.0 x 3.0

Unit weight (lbs)

12.7

Master carton type

Plain corrugated

Master carton dimensions D x W x H

25.5 x 14.0 x 7.0

Master carton weight (lbs)

53

Master carton case quantity

4

Master carton cube (cu. ft.)

1.4

UPC

661899 158021

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 3 vibrant colors: Orange, Blue, Green
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number D14412100GN

Length 100'

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Green

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

12.0 x 12.0 x 3.0

Unit weight (lbs)

12.7

Master carton type

Plain corrugated

Master carton dimensions D x W x H

25.5 x 14.0 x 7.0

Master carton weight (lbs)

53

Master carton case quantity

4

Master carton cube (cu. ft.)

1.4

UPC

661899 158045

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock[™] connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 3 vibrant colors: Orange, Blue, Green
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number D14412100OR

Length 100'

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Orange

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings **15A, 125V, 1875W**

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

12.0 x 12.0 x 3.0

Unit weight (lbs)

12.7

Master carton type

Plain corrugated

Master carton dimensions D x W x H

25.5 x 14.0 x 7.0

Master carton weight (lbs)

53

Master carton case quantity

4

Master carton cube (cu. ft.)

1.4

UPC

661899 158069

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.









Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 12/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 64 strands of 30 AWG 100% copper wire.
- Molded on Pro Lock[™] connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in 4 vibrant colors: Orange, Blue, Green & Yellow
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14412100YL**

Length 100'

Description
12/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Yellow

Gauge/Conductors

12/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

12.0 x 12.0 x 3.0

Unit weight (lbs)

12.7

Master carton type

Plain corrugated

Master carton dimensions D x W x H

25.5 x 14.0 x 7.0

Master carton weight (lbs)

53

Master carton case quantity

4

Master carton cube (cu. ft.)

1.4

UPC

661899 164923

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.





50ft 14/3 SJTW Molded Extension Cords with CGM "For Secure & Safe Connections"





Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 14/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 65 strands of 41 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- · Presented in vibrant Blue
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14414050BL**

Length **50'**

Description
14/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Blue

Gauge/Conductors

14/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

11.0 x 11.0 x 2.0

Unit weight (lbs)

4.8

Master carton type

Plain corrugated

Master carton dimensions D x W x H

21.5 x 12.0 x 8.0

Master carton weight (lbs)

30

Master carton case quantity

6

Master carton cube (cu. ft.)

1.2

UPC

661899 158113

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.





100ft 14/3 SJTW Molded Extension Cords with CGM "For Secure & Safe Connections"





Each of our Pro Lock™ Extension Cords are molded with our unique and patented Pro Lock™ female connector. When a standard extension cord with a 15A-125V, 3 conductor male plug is inserted into our Pro Lock™ connector, it won't pull apart. This prevents accidental disconnects that result in an inconvenient loss of power. Simply pull down on the connector collar to disconnect extension cords.

FEATURES

- Manufactured to 14/3 AWG (American Wire Gauge) specifications.
- Each of the three conductors contain 65 strands of 41 AWG 100% copper wire.
- Molded on Pro Lock™ connectors will not pull away from the cord body and offer extra water resistance.
- Automatic locking feature: insert male end into our Pro Lock™ connector, push together to lock & pull the collar down to unlock.
- We use high impact polycarbonate on both housing & collar on our
 Pro Lock™ connectors to guarantee hard service, extra-heavy duty use.
- Pro Lock™ Pull Strength: 80 Lbs. horizontally or vertically.
- Lighted Amber Power Check plug and indicates there is power running through the cord.
- Pro Lock™ green lighted CGM connector identifies ground continuity in the circuit.
- Our -58°F (-50°C) special coldweather PVC jacket guarantees working flexibility in temperatures well below freezing.
- Presented in vibrant Blue
- UL Listed and cUL Approved for Canada.

WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Part number **D14414100BL**

Length 100'

Description
14/3 SJTW Pro Lock Extension
Cord

Product line

Pro Lock Extension Cord

Color

Blue

Gauge/Conductors

14/3

Wire type

SJTW

Certifications

UL, cUL, OSHA

Electrical ratings 15A, 125V, 1875W

Product packaging

Cuff wrapper

Unit dimensions D x W x H (inches)

11.5 x 11.5 x 7.5

Unit weight (lbs)

9.0

Master carton type

Plain corrugated

Master carton dimensions D x W x H

24.5 x 12.5 x 8.0

Master carton weight (lbs)

38

Master carton case quantity

4

Master carton cube (cu. ft.) **1.3**

- .-

UPC

661899 158120

Custom Print Available, Absolutely Free! Allow 7 Extra Days For Delivery.