

Single Pole Devices and Temporary Power

60A, 3Phase 120/208V AC

Spider® II Temporary Power Boxes

HUBBELL

Features

- Individual GFCI modules
- TYPE 3R metallic enclosure and heavy duty, abuse resistant legs
- Standard stab termination circuit breakers with gasketed lift cover



Ordering Information

Description	Product Type	UPC	Catalog Number
Spider Box, 60A, Twist Lock	Spider II Boxes	783585940021	SCTLOM2

Standards

UL and cUL Listed

Specifications

Enclosure Type	3R, rainproof, suitable for use in damp locations
Code Compliance	NEC®, ANSI/NFPA 70

Performance

Environment	
Moisture Resistance	Indoor and outdoor wet and dry locations

Online Resources

eCatalog
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.



Single Pole Devices and Temporary Power

60A, 3Phase 120/208V AC

Spider® II Temporary Power Boxes

HUBBELL

Features

- Individual GFCI modules
- TYPE 3R metallic enclosure and heavy duty, abuse resistant legs
- Standard stab termination circuit breakers with gasketed lift cover



Ordering Information

Description	Product Type	UPC	Catalog Number
Spider Box, 60A, Straight Blade	Spider II Boxes	783585075655	SCSB0M2

Standards

UL and cUL Listed

Specifications

Enclosure Type	3R, rainproof, suitable for use in damp locations
Code Compliance	NEC®, ANSI/NFPA 70

Performance

Environment

Moisture Resistance Indoor and outdoor wet and dry locations

Online Resources

eCatalog
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

