

KAUKIT2

by Burndy
Catalog ID: KAUKIT2

Prop 65 Notice

High Strength Aluminium Alloy Tranformer Lug Kit, #6 - 250 kcmil, Tin-Plated.

Features: These Dual-Rated Lugs Are Constructed From High Strength Aluminum Alloy And Electro Tinned To Provide Low Contact Resistance, Lugs And Mounting Hardware Packaged Together In These Kits, UL Listed AL9CU Dual Rated Set Screw Terminals And CSA Certified, Ensure The Transformer Feeders And Taps Are Terminated Properly, Plated Steel Cap Screws And Hex Nuts With Captive Conical Washers Or Individual Belleville Washers, Terminal To Bus Connections Are Made Using Proper Hardware Resulting In True Torque To Pressure Performance, Compensates For Dissimilar Metal Expansion And Contraction, Hardware Packed In Plastic Bag, No Lost Hardware Prior To Installation, Conductor Type: Run: Stranded Aluminum Or Copper, Includes: (8) 1/4-20 X 3/4 IN, (8) 1/4-20 X 2 IN Hex Head, (16) 1/4-20 Hex Head, (12) KA29U Terminal, Captive To Nut Flat Washer, Transformer Kva Rating Range: 50 - 75 KVA For Single Phase, 75 - 112.5 KVA For Three Phase



Product Details

General

Application	used to provide low contact resistance
Material	Aluminum
Sub Brand	UNIVERSAL TERM
Type	Bolted Lugs & Terminals
UPC	781810600122

Conductor Related

Conductor - AL Str Size	6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
-------------------------	---

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	1
Package Contents	(12) KA29U;(8) 1/4 - 20 x 3/4 in, (8) 1/4-20 x 2 in Hex Head Bolt;(16) 1/4-20 in Hex Head Nut;Captive to Nut

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)

KAUKIT1

by Burndy
Catalog ID: KAUKIT1

Prop 65 Notice

High Strength Aluminium Alloy Tranformer Lug Kit, #14 - 2, #6 - 250 kcmil, Tin-Plated.

Features: These Dual-Rated Lugs Are Constructed From High Strength Aluminum Alloy And Electro Tinned To Provide Low Contact Resistance, Lugs And Mounting Hardware Packaged Together In These Kits, UL Listed AL9CU Dual Rated Set Screw Terminals And CSA Certified, Ensure The Transformer Feeders And Taps Are Terminated Properly, Plated Steel Cap Screws And Hex Nuts With Captive Conical Washers Or Individual Belleville Washers, Terminal To Bus Connections Are Made Using Proper Hardware Resulting In True Torque To Pressure Performance, Compensates For Dissimilar Metal Expansion And Contraction, Hardware Packed In Plastic Bag, No Lost Hardware Prior To Installation, Conductor Type: Run: Stranded Aluminum Or Copper, Includes: (8) 1/4-20 X 3/4 IN Hex Head, (8) 1/4-20 Hex Head, (8) KA2U, (4) KA29U Terminal, Captive To Nut Flat Washer, Transformer Kva Rating Range: 15 - 37.5 KVA For Single Phase, 15 - 45 KVA For Three Phase



Product Details

General

Application	used to provide low contact resistance
Material	Aluminum
Sub Brand	UNIVERSAL TERM
Type	Bolted Lugs & Terminals
UPC	781810600115

Conductor Related

Conductor - AL Str Size	8 AWG;6 AWG;4 AWG;3 AWG;2 AWG;1 AWG;1/0 AWG;2/0 AWG;3/0 AWG;4/0 AWG;250 kcmil
-------------------------	---

Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Listed Direct Burial	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	EX
UL Listed	No

Logistics

Minimum Pack Quantity	1
Package Contents	(8) KA2U , (4) KA29U;(8) 1/4-20 x 3/4 in Hex Head Bolt;(8) 1/4-20 in Hex Head Nut;Captive to Nut

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)