

# Cable, Cord and Hose Reels



## Stainless Steel Cord Reels



**HBLSS45123**

Description	Amps	Volts	Cable Length Feet (m)	Cable Type	Weight Lbs. (kg)	Catalog Number
Stainless steel reel without cord ends	20	125	45 (13.7)	#12/3 SJEO	30 (14)	<b>HBLSS45123</b>

Note: For indoor non-weathertight applications only.



## Industrial Lighted Cord Reels, 45 Ft. (13.7m) - 16/3 AWG SJEO Cable



**HBLI45163LED**

Cord End	Amps	Volts AC	Watts (Max)	Weight Lbs. (kg)	Catalog Number
LED hand lamp, with end light, white reel.	0.07	120	8 + 1	22.9 (10.4)	<b>HBLI45163LED</b>
Fluorescent hand lamp, white reel.	0.3	120	13	22.9 (10.4)	<b>HBLI45163FL</b>
Incandescent hand lamp, white reel.	0.8	125	100	22.9 (10.4)	<b>HBLI45163IN</b>

Note: Supplied with 5 ft. power supply cord with HBL5266C, 15A straight blade plug.

For shorter cable lengths, modify length indication in catalog number (i.e. HBLIXX); 35ft & 25ft lengths are available.

For yellow reel, add 'Y' suffix to catalog number.

## Accessories

Description	Amps	Volts AC	Watts (Max)	Weight Lbs. (kg)	Catalog Number
Replacement stop.	—	—	—	.2 (.09)	<b>HBL16BS</b>
Replacement LED hand lamp.	0.07	120	8 + 1	1 (.5)	<b>HBL16LEDR*</b>
Replacement fluorescent hand lamp.	0.3	120	13	1 (.5)	<b>HBL16FLR</b>
Replacement incandescent hand lamp.	0.8	125	100	1 (.5)	<b>HBL16INR</b>

Note: \*cETLus Listed by INTERTEK.



**HBLC40182LED**



**HBLC25143IN**



**HBLI45163FL**



**HBLI45163IN**



## Commercial Lighted Cord Reels



**HBLC40182AFL**

Description	Amps	Volts AC	Cable Length Feet (m)	Cable Type	Watts (Max)	Weight Lbs. (kg)	Catalog Number
White Reel with LED hand lamp, with flashlight end.	0.65	125	40 (12.2)	#18/2 SJTOW	8 + 1	8.2 (3.7)	<b>HBLC40182LED</b>
White Reel with non-metallic incandescent hand lamp and automatic shut off switch.	0.6	125	25 (7.6)	#16/3 SJT	75	9.0 (4.1)	<b>HBLC25163AIN**</b>
Yellow Reel with metallic incandescent hand lamp with receptacle.	13	125	25 (7.6)	#14/3 SJT	1,625	9.5 (4.3)	<b>HBLC25143IN</b>
White Reel with fluorescent hand lamp and automatic shut off switch.	0.3	120	40 (12.2)	#18/2 SJTOW	13	8.2 (3.7)	<b>HBLC40182AFL**</b>
White Reel with fluorescent hand lamp and in-line receptacle.	10	120	40 (12.2)	#16/3 SJT	1,200	9.0 (4.1)	<b>HBLC40163FL</b>

Note: \*\*Allows the electrical cord reel installation to conform to Article 511 of the National Electric Code concerning installation of electrical devices in commercial garages, repair facilities and storage locations by positioning the switch above the defined area where hazardous fumes may collect.



**HBLC40163FL**

Dimensions in Inches (mm)



INTERTEK and the Intertek logo are registered trademarks of Intertek Group plc.