

PB101



UPC Code : 078477085714

Country Of Origin : Mexico

The Box 50A 125/250 Volt Temporary Portable Power Distribution Center w/ 6 L5-20R Locking GFCI Protected Outlets and One L6-30R Locking Non-GFCI Protected Outlet - Yellow

Leviton Power Centers feature a variety of GFCI protected outlets and standard outlets to accommodate the variety of portable power equipment being used throughout the jobsite.

Technical Information

Electrical Specifications

Dielectric Voltage : Withstands 1500V per UL498

Grounding : GFCI Grounding

Power Center Rating : 50A 125/250 Volt

SCCR : 2 kA

Temperature Rise : Max 30C after 50 cycles OL at 150 percent rated current

Trip Level : 5mA plus or minus 1mA

Environmental Specifications

Housing Rating : UL Listed for Outdoor Use

Operating Temperature : -35C to +66C

Material Specifications

Color : Yellow

Housing Material : Reinforced Metal

Mechanical Specifications

20 Amp Outlets : 6 L5-20R Locking GFCI Protected

30 Amp 250V Outlet : One L6-30R Locking Non-GFCI Protected

Feed-Through Outlet : 50A 125/250 Volt 3P 4W, Grounding Non-NEMA

Power Inlet : 50A 125/250 Volt 3P 4W, Grounding Non-NEMA

Product ID : Ratings and NEMA I.D. permanently marked on device

Terminal ID : Brass-Hot, Green-Ground, Silver-Neutral

Product Features

Color : Yellow

Standards and Certifications

ANSI : C-73

CSA C22.2 : File LR-57811

NEMA : WD-6

NOM : 057

OSHA : Reg 20, Part 1926, Subpart K for open-neutral GFCI

UL 943 : Class A (GFCI)

UL Listed : E-48380

Warranty : 1-Year Limited

