

SIEMENS

Table of Contents

SIE-Q120	Page 2
SIE-Q220	Page 3
SIE-Q320	Page 4
SIE-Q125	Page 5
SIE-Q225	Page 6
SIE-Q325	Page 7
SIE-Q130	Page 8
SIE-Q230	Page 9
SIE-Q330	Page 10
SIE-Q140	Page 11
SIE-Q240	Page 12
SIE-Q340	Page 13
SIE-Q150	Page 14
SIE-Q250	Page 15
SIE-Q350	Page 16
SIE-Q160	Page 17
SIE-Q260	Page 18
SIE-Q360	Page 19

BREAKER 20A 1P 120V 10K QP SINGLE POLE 20 AMP
BREAKER 10 K AIC SIEMENS



Number of poles	1
Suitability for operation	Electrical Distribution
Electricity	
Continuous current rated value	20 A
Model	
Product brand name	SIEMENS
Type of electrical connection	PLUG-IN
Mechanical Design	
Depth [in]	12.8 in
Design of the product	QP/MP
Height [in]	3.5 in
Width [in]	3.6 in
General product approval	
Standard	UL 489
last modified:	03/08/2020

BREAKER 20A 2P 120/240V 10K QP10 KAICSIEMENS



Number of poles	2
Suitability for operation	Electrical Distribution
Electricity	
Continuous current rated value	20 A
Model	
Product brand name	SIEMENS
Type of electrical connection	PLUG-IN
Mechanical Design	
Depth [in]	3 in
Design of the product	QP/MP
Height [in]	3 in
Width [in]	2 in
General product approval	
Standard	UL 489
last modified:	03/05/2020



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Type QP/MP, 3-Pole, 240VAC are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: QP/MP Application: Electrical Distribution Standard: UL 489 Voltage Rating: 240V Amperage Rating: 20A Trip Range: Thermal Magnetic Interrupt Rating: 10 AIC Number Of Poles: 3P

Number of poles	3
Suitability for operation	Electrical Distribution
Electricity	
Continuous current rated value	20 A
Model	
Product brand name	SIEMENS
Type of electrical connection	PLUG-IN
Mechanical Design	
Depth [in]	12.8 in
Design of the product	QP/MP
Height [in]	3.4 in
Width [in]	3.7 in
General product approval	
Standard	UL 489
last modified:	03/30/2020



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Type QP/MP 1-pole 10k are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: QP/MP Application: Electrical Distribution Standard: UL 489 Voltage Rating: 120V Amperage Rating: 25A Trip Range: Thermal Magnetic Interrupt Rating: 1.0 AIC Number Of Poles: 1P

General technical data	
number of poles	1
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	25 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	13 in
design of the product	QP/MP
height [in]	3.5 in
width [in]	3 in
General product approval	
standard	UL 489

last modified:

4/4/2023 



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Type QP/MP, 2-Pole, 120/240VAC are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: QP/MP Application: Electrical Distribution Standard: UL 489 Voltage Rating: 120/240 V Amperage Rating: 25A Trip Range: Thermal Magnetic Interrupt Rating: 10 AIC Number Of Poles: 2P

General technical data	
number of poles	2
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	25 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	2 in
width [in]	3 in
General product approval	
standard	UL 489

last modified:

1/6/2021



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Type QP/MP, 3-Pole, 240VAC are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: QP/MP Application: Electrical Distribution Standard: UL 489 Voltage Rating: 240V Amperage Rating: 25A Trip Range: Thermal Magnetic Interrupt Rating: 10 AIC Number Of Poles: 3P

General technical data	
number of poles	3
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	25 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the	QP/MP
product height [in]	3 in
width [in]	3 in
General product approval	
standard	UL 489

last modified:

1/6/2021



BREAKER 30A 1P 120V 10K QP

General technical data	
number of poles	1
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	30 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	3 in
width [in]	1 in
General product approval	
standard	UL 489

last modified:

1/6/2021 



BREAKER 30A 2P 120/240V 10K QP

General technical data	
number of poles	2
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	30 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	2 in
width [in]	3 in
General product approval	
standard	UL 489

last modified:

1/7/2021 



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Type QP/MP, 3-Pole, 240VAC are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: QP/MP Application: Electrical Distribution Standard: UL 489 Voltage Rating: 240V Amperage Rating: 30A Trip Range: Thermal Magnetic Interrupt Rating: 10 AIC Number Of Poles: 3P

General technical data	
number of poles	3
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	30 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the	QP/MP
product height [in]	3 in
width [in]	3 in
General product approval	
standard	UL 489

last modified:

1/6/2021



BREAKER 40A 1P 120V 10K QP10 KAIC

General technical data	
number of poles	1
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	40 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	3 in
width [in]	1 in
General product approval	
standard	UL 489

last modified:

1/6/2021



BREAKER 40A 2P 120/240V 10K QP10 KAIC SIEMENS

General technical data	
number of poles	2
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	40 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	2 in
width [in]	3 in
General product approval	
standard	UL 489

last modified: 1/7/2021 



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Type QP/MP, 3-Pole, 240VAC are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: QP/MP Application: Electrical Distribution Standard: UL 489 Voltage Rating: 240V Amperage Rating: 40A Trip Range: Thermal Magnetic Interrupt Rating: 10 AIC Number Of Poles: 3P

General technical data	
number of poles	3
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	40 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	13 in
design of the	QP/MP
product height [in]	3.4 in
width [in]	4 in
General product approval	
standard	UL 489

last modified:

4/4/2023 



BREAKER 50A 1P 120V 10K QP10 KAIC

General technical data	
number of poles	1
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	50 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	3 in
width [in]	1 in
General product approval	
standard	UL 489

last modified:

1/6/2021



BREAKER 50A 2P 120/240V 10K QP10 KAIC

General technical data	
number of poles	2
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	50 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	2 in
width [in]	3 in
General product approval	
standard	UL 489

last modified:

1/6/2021



BREAKER 50A 3P 240V 10K QP

General technical data	
number of poles	3
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	50 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	7 in
design of the product	QP/MP
height [in]	4 in
width [in]	6 in
General product approval	
standard	UL 489

last modified: 1/6/2021 



BREAKER 60A 1P 120V 10K QP10 KAIC

General technical data	
number of poles	1
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	60 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	3 in
width [in]	1 in
General product approval	
standard	UL 489

last modified:

1/6/2021



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Type QP/MP, 2-Pole, 120/240VAC are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: QP/MP Application: Electrical Distribution Standard: UL 489 Voltage Rating: 120/240 V Amperage Rating: 60A Trip Range: Thermal Magnetic Interrupt Rating: 10 AIC Number Of Poles: 2P

General technical data	
number of poles	2
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	60 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the product	QP/MP
height [in]	2 in
width [in]	3 in
General product approval	
standard	UL 489

last modified:

1/7/2021 



Siemens Low Voltage Residential Circuit Breakers Miniature Thermal Mag Circuit Breakers - Type QP/MP, 3-Pole, 240VAC are Circuit Protection Load Center Mains, Feeders, and Miniature Circuit Breakers. Type: QP/MP Application: Electrical Distribution Standard: UL 489 Voltage Rating: 240V Amperage Rating: 60A Trip Range: Thermal Magnetic Interrupt Rating: 10 AIC Number Of Poles: 3P

General technical data	
number of poles	3
suitability for operation	Electrical Distribution
Electricity	
continuous current rated value	60 A
Model	
product brand name	SIEMENS
type of electrical connection	PLUG-IN
Mechanical Design	
depth [in]	3 in
design of the	QP/MP
product height [in]	3 in
width [in]	3 in
General product approval	
standard	UL 489

last modified:

1/6/2021 