

Table of Contents

SIE-SN1224L1125	Page 2
SIE-SNW1224L1125	Page 3
SIE-SN2040L1125	Page 4
SIE-SNW2040L1125	Page 5
SIE-SN3048L1125	Page 6
SIE-SNW3048L1125	Page 7
SIE-SN2040L1150	Page 8
SIE-SNW2040L1150	Page 9
SIE-SN1224L1200	Page 10
SIE-SNW1224L1200	Page 11
SIE-SN3048L1200	Page 12
SIE-SNW3048L1200	Page 13
SIE-SN4040L1200	Page 14
SIE-SNW4040L1200	Page 15
SIE-SN4264L1225	Page 16
SIE-SNW4264L1225	Page 17
SIE-SN5482L1225	Page 18

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 12 1-INCH SPACES ALLOWING
MAX 24 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1
ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	24
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	125
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	12
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 12 1-INCH SPACES ALLOWING
MAX 24 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R
ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	24
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	125
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	12
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 20 1-INCH SPACES ALLOWING
MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1
ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	40
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	125
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	20
General product approval	
certificate of suitability	UL

last modified: 7/9/2021 

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 20 1-INCH SPACES ALLOWING
MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R
ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	40
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	125
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	20
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 30 1-INCH SPACES ALLOWING
MAX 48 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1
ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	48
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	125
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	30
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 30 1-INCH SPACES ALLOWING
MAX 48 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (125A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R
ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	48
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	125
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	30
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 20 1-INCH SPACES ALLOWING
MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (150A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1
ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	40
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	150
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	20
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 



SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 20 1-INCH SPACES ALLOWING MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (150A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	40
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	150
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	20
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 



SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 12 1-INCH SPACES ALLOWING MAX 24 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1 ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	24
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	12
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 



SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 12 1-INCH SPACES ALLOWING MAX 24 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	24
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	12
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 30 1-INCH SPACES ALLOWING
MAX 48 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1
ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	48
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	30
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 



SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 30 1-INCH SPACES ALLOWING MAX 48 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	48
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	30
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 

SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES
ASSEMBLED LOAD CENTER. MAIN LUG WITH 40 1-INCH SPACES ALLOWING
MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A)
100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1
ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	40
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	40
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 



SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 40 1-INCH SPACES ALLOWING MAX 40 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (200A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	40
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	200
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	40
General product approval	
certificate of suitability	UL

last modified:

7/9/2021



SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 42 1-INCH SPACES ALLOWING MAX 64 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (225A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1 ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	64
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	225
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	42
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 



SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 42 1-INCH SPACES ALLOWING MAX 64 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (225A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 3R ENCLOSURE FOR OUTDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	64
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	225
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	240 V
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	42
General product approval	
certificate of suitability	UL

last modified:

7/9/2021



SIEMENS LOW VOLTAGE PLUG-ON NEUTRAL READY STANDARD SERIES ASSEMBLED LOAD CENTER. MAIN LUG WITH 54 1-INCH SPACES ALLOWING MAX 82 CIRCUITS. 1-PHASE 3-WIRE SYSTEM RATED 120/240V (225A) 100KAIC. SPECIAL FEATURES: ALUMINUM BUS, GREY TRIM NEMA TYPE 1 ENCLOSURE FOR INDOOR USE.

General technical data	
configuration of the busbars	ALUMINUM BUS
number of circuits in a trunking unit	82
phase number	1
suitability for operation	RESIDENTIAL AND LIGHT COMMERCIAL ELECTRIC DISTRIBUTION
Electricity	
ampacity	225
voltage between phase and Ground (GND) rated	A
value voltage between phase and phase rated value	120 V
Model	
240 V	
product brand name	SIEMENS
product sub brand name	LOAD CENTERS
product type designation	PLUG-ON NEUTRAL READY STANDARD SERIES
special product feature	GREY TRIM
Mechanical Design	
number of modular width units for installation width	54
General product approval	
certificate of suitability	UL

last modified:

7/9/2021 