

## T4A 4 CONDUCTOR AL/CU



Fig. 1



Fig. 2



Fig. 3



Fig. 4

- Manufactured from high strength 6061-T6 aluminum alloy.
- Electro-tin plated.
- UL 486A/B 90° C Listed and is CSA certified.
- Suitable for use in circuits rated 35KV or less; proper high voltage spacing and insulation techniques must be used.
- Dual Rated for Copper and Aluminum Conductor.
- Chamfered wire entry provides ease of installation.
- Must be mounted with a minimum of 4 bolts.
- UL File E6207
- \* Mounting hole spacing from side to side, hole to hole is .875".

Item ID	Figure Number	Conductor Range	Bolt/Stud Size	Mounting Hole Spacing	Length	Width	Height	Hex Size	Standard Package	NAED/UPC Number
T4A4-250N	* 1	250 kcmil-6 AWG	1/2	1-3/4	4.0000	3.6870	1.1870	5/16	1	0783669912159
T4A4-350N	* 3	350 kcmil-6 AWG	1/2	1-3/4	4.3130	3.9370	1.3750	5/16	1	0783669912203
T4A4-600N	* 3	600 kcmil-2 AWG	1/2	1-3/4	5.5000	5.0000	1.5000	1/2	1	0783669912265
T4A4-800N	* 2	800 kcmil-300 kcmil	1/2	1-3/4	5.9700	6.0000	1.8130	1/2	1	0783669912319
T4A4-1000N	* 4	1000 kcmil-350 kcmil	1/2	1-3/4	5.9700	6.5000	1.8130	1/2	1	0783669912357